

Eagle Window & Door

Ascent[®] Outswing French Door Sidelite (SL1)

2068 Tested Size at DP +60, -75 Mono

Series 05 Ascent Clad Outswing French Door SL1 Sidelite H/P Sill

Glass Type	Divided Light Options	U-VAL	SHGC	VLT	CR	Energy Star Zone
HarborMaster™ Monolithic Glass Clear 10.3 mm	No Between-glass Grilles or MDL	0.75	0.45	0.49	15	1
	7/8" CDL	0.75	0.40	0.44	15	1
	1-1/8" & 1-1/2" CDL	0.75	0.35	0.39	15	1
HarborMaster™ Monolithic Glass Bronze Tint 11.1 mm	No Between-glass Grilles or MDL	0.75	0.33	0.29	15	1
	7/8" CDL	0.75	0.30	0.26	15	1
	1-1/8" & 1-1/2" CDL	0.75	0.27	0.23	15	1
HarborMaster™ Monolithic Glass Gray Tint 11.1 mm	No Between-glass Grilles or MDL	0.75	0.32	0.25	15	1
	7/8" CDL	0.75	0.29	0.23	15	1
	1-1/8" & 1-1/2" CDL	0.75	0.26	0.20	15	1
HarborMaster™ Monolithic Glass Low-E 10.1 mm	No Between-glass Grilles or MDL	0.75	0.27	0.39	15	1
	7/8" CDL	0.75	0.24	0.35	15	1
	1-1/8" & 1-1/2" CDL	0.75	0.21	0.31	15	1

U-Factor - Rate of Heat Loss = 1/R

SHGC - Solar Heat Gain Coefficient

VLT- Visible Light Transmittance

CR - Condensation Resistance