

<b>Product</b>	<b>High-Performance™ Low-E4® without Divided Lights</b>	<b>High-Performance™ Low-E4® with Divided Lights</b>
<b>Extended Half Circle Casement Windows - Operating (24 1/8" x 48")</b>		
U-Factor <sup>1</sup>	0.32	0.32
SHGC <sup>2</sup>	0.28	0.25
VT <sup>3</sup>	0.47	0.42
<b>Extended Half Circle French Casement Windows - Operating (56 1/2" x 71 7/8")</b>		
U-Factor <sup>1</sup>	0.32	0.32
SHGC <sup>2</sup>	0.28	0.25
VT <sup>3</sup>	0.47	0.42
<b>Extended Half Circle Fixed Casement/Picture Windows (up to 17 sq. ft.)</b>		
U-Factor <sup>1</sup>	0.31	0.31
SHGC <sup>2</sup>	0.32	0.29
VT <sup>3</sup>	0.55	0.49
<b>Extended Half Circle Monumetal Single-Hung Windows</b>		
U-Factor <sup>1</sup>		
SHGC <sup>2</sup>	<i>Information not available</i>	
VT <sup>3</sup>		
<b>Specialty Shaped Windows (units up to 17 sq. ft.)</b>		
U-Factor <sup>1</sup>	0.30	0.30
SHGC <sup>2</sup>	0.37	0.33
VT <sup>3</sup>	0.64	0.57
<b>Extended Half Circle Inswing Hinged Doors</b>		
U-Factor <sup>1</sup>	0.32	0.33
SHGC <sup>2</sup>	0.22	0.19
VT <sup>3</sup>	0.37	0.31
<b>Extended Half Circle Inswing Fixed Doors &amp; Sidelites</b>		
U-Factor <sup>1</sup>	0.35	0.35
SHGC <sup>2</sup>	0.15	0.15
VT <sup>3</sup>	0.24	0.23
<b>Extended Half Circle Outswing Hinged Doors</b>		
U-Factor <sup>1</sup>	0.32	0.33
SHGC <sup>2</sup>	0.22	0.19
VT <sup>3</sup>	0.37	0.31
<b>Extended Half Circle Outswing Fixed Doors &amp; Sidelites</b>		
U-Factor <sup>1</sup>	0.34	0.34
SHGC <sup>2</sup>	0.15	0.14
VT <sup>3</sup>	0.24	0.23

**NOTES**

<sup>1</sup> U-Factor defines the amount of heat loss through the total unit in BTU/hr sq. ft.<sup>2</sup>. °F. The lower the value, the less heat is lost through the entire product.

<sup>2</sup> Solar Heat Gain Coefficient (SHGC) defines the fraction of solar radiation admitted through the glass both directly transmitted and absorbed and subsequently released inward. The lower the value, the less heat is transmitted through the product.

<sup>3</sup> Visible Transmittance (VT) measures how much light comes through a product (glass and frame). The higher the value, from 0 to 1, the more daylight the product lets in over the product's total unit area. Visible Transmittance is measured over the 380 to 760 nanometer portion of the solar spectrum.

*This data is accurate as of February 20, 2009. Due to ongoing product changes, updated test results, or new industry standards, this data may change over time.*

These specialty products vary from other Eagle products.  
See your Eagle dealer for more details.

**Eagle Window & Door**

For more information or for the dealer nearest you, call 800.453.3633 or visit EagleWindow.com

Feb-09