



## Talon® Radius Single-Hung Windows (Single Unit) Opening Tables

Call Size	Width (Inches)	Height (Inches)	Radius (Inches)	Meets Egress Req.	Sq. Ft. Clear Opening	Clear Opening (Inches)		Sq. Ft. Vent	Sq. Ft. Daylight Opening	Bottom Sash Glass Size (Inches)		Floor to Sill Height (Inches)
						Width	Height			Width	Height	
2030	24	36	36	No	1.50	19 11/16	11	1.50	3.01	17 15/16	14	49 7/16
2034	24	40	36	No	1.78	19 11/16	13	1.78	3.48	17 15/16	16	45 7/16
2040	24	48	36	No	2.32	19 11/16	17	2.32	4.42	17 15/16	20	37 7/16
2046	24	54	36	No	2.73	19 11/16	20	2.73	5.13	17 15/16	23	31 7/16
2049	24	57	36	No	2.94	19 11/16	22	2.94	5.48	17 15/16	24 1/2	28 7/16
2050	24	60	36	No	3.14	19 11/16	23	3.14	5.83	17 15/16	26	25 7/16
2051	24	61	36	No	3.21	19 11/16	24	3.21	5.95	17 15/16	26 1/2	24 7/16
2056	24	66	36	No	3.56	19 11/16	26	3.56	6.54	17 15/16	29	19 7/16
2060	24	72	36	No	3.97	19 11/16	29	3.97	7.24	17 15/16	32	13 7/16
2430	28	36	36	No	1.70	23 11/16	10 5/16	1.70	3.69	21 15/16	14	49 7/16
2434	28	40	36	No	2.03	23 11/16	12 5/16	2.03	4.27	21 15/16	16	45 7/16
2440	28	48	36	No	2.68	23 11/16	16 5/16	2.68	5.44	21 15/16	20	37 7/16
2446	28	54	36	No	3.18	23 11/16	19 5/16	3.18	6.31	21 15/16	23	31 7/16
2449	28	57	36	No	3.42	23 11/16	20 13/16	3.42	6.75	21 15/16	24 1/2	28 7/16
2450	28	60	36	No	3.67	23 11/16	22 5/16	3.67	7.18	21 15/16	26	25 7/16
2451	28	61	36	No	3.75	23 11/16	22 13/16	3.75	7.33	21 15/16	26 1/2	24 7/16
2456	28	66	36	No	4.16	23 11/16	25 5/16	4.16	8.05	21 15/16	29	19 7/16
2460	28	72	36	No	4.66	23 11/16	28 5/16	4.66	8.93	21 15/16	32	13 7/16
2630	30	36	36	No	1.77	25 11/16	9 59/64	1.77	4.03	23 15/16	14	49 7/16
2634	30	40	36	No	2.13	25 11/16	11 59/64	2.13	4.66	23 15/16	16	45 7/16
2640	30	48	36	No	2.84	25 11/16	15 59/64	2.84	5.94	23 15/16	20	37 7/16
2646	30	54	36	No	3.37	25 11/16	18 59/64	3.37	6.89	23 15/16	23	31 7/16
2649	30	57	36	No	3.64	25 11/16	20 27/64	3.64	7.37	23 15/16	24 1/2	28 7/16
2650	30	60	36	No	3.91	25 11/16	21 59/64	3.91	7.85	23 15/16	26	25 7/16
2651	30	61	36	No	4.00	25 11/16	22 27/64	4.00	8.01	23 15/16	26 1/2	24 7/16
2656	30	66	36	No	4.45	25 11/16	24 59/64	4.45	8.81	23 15/16	29	19 7/16
2660	30	72	36	No	4.98	25 11/16	27 59/64	4.98	9.76	23 15/16	32	13 7/16
2830	32	36	36	No	1.82	27 11/16	9 31/64	1.82	4.36	25 15/16	14	49 7/16
2834	32	40	36	No	2.21	27 11/16	11 31/64	2.21	5.05	25 15/16	16	45 7/16
2840	32	48	36	No	2.98	27 11/16	15 31/64	2.98	6.43	25 15/16	20	37 7/16
2846	32	54	36	No	3.55	27 11/16	18 31/64	3.55	7.47	25 15/16	23	31 7/16
2849	32	57	36	No	3.84	27 11/16	19 63/64	3.84	7.99	25 15/16	24 1/2	28 7/16
2850	32	60	36	No	4.13	27 11/16	21 31/64	4.13	8.51	25 15/16	26	25 7/16
2851	32	61	36	No	4.23	27 11/16	21 63/64	4.23	8.69	25 15/16	26 1/2	24 7/16
2856	32	66	36	No	4.71	27 11/16	24 31/64	4.71	9.55	25 15/16	29	19 7/16
2860	32	72	36	No	5.28	27 11/16	27 31/64	5.28	10.59	25 15/16	32	13 7/16
3030	36	36	36	No	1.87	31 11/16	8 1/2	1.87	5.00	29 15/16	14	49 7/16
3034	36	40	36	No	2.31	31 11/16	10 1/2	2.31	5.80	29 15/16	16	45 7/16
3040	36	48	36	No	3.19	31 11/16	14 1/2	3.19	7.41	29 15/16	20	37 7/16
3046	36	54	36	No	3.85	31 11/16	17 1/2	3.85	8.61	29 15/16	23	31 7/16
3049	36	57	36	No	4.18	31 11/16	19	4.18	9.22	29 15/16	24 1/2	28 7/16
3050	36	60	36	No	4.51	31 11/16	20 1/2	4.51	9.82	29 15/16	26	25 7/16
3051	36	61	36	No	4.62	31 11/16	21	4.62	10.02	29 15/16	26 1/2	24 7/16
3056	36	66	36	No	5.17	31 11/16	23 1/2	5.17	11.02	29 15/16	29	19 7/16
3060	36	72	36	Yes	5.83	31 11/16	26 1/2	5.83	12.23	29 15/16	32	13 7/16

**Notes:**

Floor to sill height is based on structural header heights of 6' 10-1/2" and is calculated from the top of the subfloor to the top of the inside sill stop.

Egress Requirements: 5.7 sq. ft. minimum clear opening area, 20" minimum clear opening width, 24" minimum clear opening height, 44" maximum floor to sill height.

Code restrictions may vary depending on your local building codes.

If glass is positioned within 18" of the floor, safety/tempered glass may be required by code.

Eagle Window & Door reserves the right to change specifications without notice.

12.2007