

Eagle Window & Door

Opening Tables

Talon® Cottage Double-Hung Windows

Unit No.	Width (Inches)	Height (Inches)	Meets Egress Req.	Sq. Ft. Clear Opening	Clear Opening (Inches)		Sq. Ft. Vent	Sq. Ft. Daylight Opening	Glass Size (Inches)			Floor to Sill Height (Inches)
					Width	Height			Width	US Glass Height	LS Glass Height	
1846	20	54	No	1.61	15 11/16	14.75	1.61	3.95	13 15/16	17	29	31 7/16
1849	20	57	No	1.77	15 11/16	16.25	1.77	4.22	13 15/16	18 1/2	30 1/2	28 7/16
1850	20	60	No	1.93	15 11/16	17.75	1.93	4.49	13 15/16	20	32	25 7/16
1851	20	61	No	1.99	15 11/16	18.25	1.99	4.58	13 15/16	20 1/2	32 1/2	24 7/16
1856	20	66	No	2.26	15 11/16	20.75	2.26	5.03	13 15/16	23	35	19 7/16
1860	20	72	No	2.59	15 11/16	23.75	2.59	5.57	13 15/16	26	38	13 7/16
2046	24	54	No	2.02	19 11/16	14.75	2.02	5.18	17 15/16	17	29	31 7/16
2049	24	57	No	2.22	19 11/16	16.25	2.22	5.53	17 15/16	18 1/2	30 1/2	28 7/16
2050	24	60	No	2.43	19 11/16	17.75	2.43	5.88	17 15/16	20	32	25 7/16
2051	24	61	No	2.50	19 11/16	18.25	2.50	6.00	17 15/16	20 1/2	32 1/2	24 7/16
2056	24	66	No	2.84	19 11/16	20.75	2.84	6.59	17 15/16	23	35	19 7/16
2060	24	72	No	3.25	19 11/16	23.75	3.25	7.29	17 15/16	26	38	13 7/16
2446	28	54	No	2.43	23 11/16	14.75	2.43	6.40	21 15/16	17	29	31 7/16
2449	28	57	No	2.67	23 11/16	16.25	2.67	6.83	21 15/16	18 1/2	30 1/2	28 7/16
2450	28	60	No	2.92	23 11/16	17.75	2.92	7.27	21 15/16	20	32	25 7/16
2451	28	61	No	3.00	23 11/16	18.25	3.00	7.42	21 15/16	20 1/2	32 1/2	24 7/16
2456	28	66	No	3.41	23 11/16	20.75	3.41	8.14	21 15/16	23	35	19 7/16
2460	28	72	No	3.91	23 11/16	23.75	3.91	9.01	21 15/16	26	38	13 7/16
2646	30	54	No	2.63	25 11/16	14.75	2.63	7.01	23 15/16	17	29	31 7/16
2649	30	57	No	2.90	25 11/16	16.25	2.90	7.49	23 15/16	18 1/2	30 1/2	28 7/16
2650	30	60	No	3.17	25 11/16	17.75	3.17	7.96	23 15/16	20	32	25 7/16
2651	30	61	No	3.26	25 11/16	18.25	3.26	8.12	23 15/16	20 1/2	32 1/2	24 7/16
2656	30	66	No	3.70	25 11/16	20.75	3.70	8.92	23 15/16	23	35	19 7/16
2660	30	72	No	4.24	25 11/16	23.75	4.24	9.88	23 15/16	26	38	13 7/16
2846	32	54	No	2.84	27 11/16	14.75	2.84	7.62	25 15/16	17	29	31 7/16
2849	32	57	No	3.12	27 11/16	16.25	3.12	8.14	25 15/16	18 1/2	30 1/2	28 7/16
2850	32	60	No	3.41	27 11/16	17.75	3.41	8.66	25 15/16	20	32	25 7/16
2851	32	61	No	3.51	27 11/16	18.25	3.51	8.83	25 15/16	20 1/2	32 1/2	24 7/16
2856	32	66	No	3.99	27 11/16	20.75	3.99	9.70	25 15/16	23	35	19 7/16
2860	32	72	No	4.57	27 11/16	23.75	4.57	10.74	25 15/16	26	38	13 7/16
3046	36	54	No	3.25	31 11/16	14.75	3.25	8.84	29 15/16	17	29	31 7/16
3049	36	57	No	3.58	31 11/16	16.25	3.58	9.45	29 15/16	18 1/2	30 1/2	28 7/16
3050	36	60	No	3.91	31 11/16	17.75	3.91	10.05	29 15/16	20	32	25 7/16
3051	36	61	No	4.02	31 11/16	18.25	4.02	10.25	29 15/16	20 1/2	32 1/2	24 7/16
3056	36	66	No	4.57	31 11/16	20.75	4.57	11.25	29 15/16	23	35	19 7/16
3060	36	72	No	5.23	31 11/16	23.75	5.23	12.46	29 15/16	26	38	13 7/16
3246	38	54	No	3.45	33 11/16	14.75	3.45	9.45	31 15/16	17	29	31 7/16
3249	38	57	No	3.80	33 11/16	16.25	3.80	10.10	31 15/16	18 1/2	30 1/2	28 7/16
3250	38	60	No	4.15	33 11/16	17.75	4.15	10.74	31 15/16	20	32	25 7/16
3251	38	61	No	4.27	33 11/16	18.25	4.27	10.96	31 15/16	20 1/2	32 1/2	24 7/16
3256	38	66	No	4.85	33 11/16	20.75	4.85	12.03	31 15/16	23	35	19 7/16
3260	38	72	No	5.56	33 11/16	23.75	5.56	13.32	31 15/16	26	38	13 7/16
3446	40	54	No	3.66	35 11/16	14.75	3.66	10.06	33 15/16	17	29	31 7/16
3449	40	57	No	4.03	35 11/16	16.25	4.03	10.75	33 15/16	18 1/2	30 1/2	28 7/16
3450	40	60	No	4.40	35 11/16	17.75	4.40	11.44	33 15/16	20	32	25 7/16
3451	40	61	No	4.52	35 11/16	18.25	4.52	11.67	33 15/16	20 1/2	32 1/2	24 7/16
3456	40	66	No	5.14	35 11/16	20.75	5.14	12.81	33 15/16	23	35	19 7/16
3460	40	72	No	5.89	35 11/16	23.75	5.89	14.18	33 15/16	26	38	13 7/16
3846	44	54	No	4.07	39 11/16	14.75	4.07	11.29	37 15/16	17	29	31 7/16
3849	44	57	No	4.48	39 11/16	16.25	4.48	12.06	37 15/16	18 1/2	30 1/2	28 7/16
3850	44	60	No	4.89	39 11/16	17.75	4.89	12.83	37 15/16	20	32	25 7/16
3851	44	61	No	5.03	39 11/16	18.25	5.03	13.08	37 15/16	20 1/2	32 1/2	24 7/16
3856	44	66	No	5.72	39 11/16	20.75	5.72	14.36	37 15/16	23	35	19 7/16
3860	44	72	No	6.55	39 11/16	23.75	6.55	15.90	37 15/16	26	38	13 7/16

Notes:

Floor to sill height is based on structural header heights of 6' 10-1/2" and is calculated from the top of the subfloor to the top of the inside sill stop.
 Egress Requirements: 5.7 sq. ft. minimum clear opening area, 20" minimum clear opening width, 24" minimum clear opening height, 44" maximum floor to sill height.

Code restrictions may vary depending on your local building codes.

If glass is positioned within 18" of the floor, safety/tempered glass may be required by code.

Eagle Window & Door reserves the right to change specifications without notice.

Rev. 12/07