

# Eagle Window & Door

## Ascent<sup>®</sup> Inswing French Door Sidelite with Handicap Sill (SL1)

2068 Tested Size at DP 40

Series 05 Ascent Clad Inswing French Door SL1 Sidelite H/C Sill

Glass Type	Divided Light Options	U-VAL	SHGC	VLТ	CR	Energy Star Zone
High-Performance™ Low-E4™ 3.1mm / 13mm / 3.1mm	No Between-glass Grilles or MDL	0.33	0.24	0.41	58	2
	7/8" CDL	0.33	0.21	0.36	58	2
	1-1/8" & 1-1/2" CDL	0.33	0.19	0.32	58	2
	5/8" Between-glass Grilles	0.34	0.21	0.36	58	2
	1" Between-glass Grilles	0.34	0.21	0.36	58	2
	5/8" MDL	0.34	0.21	0.36	58	2
	7/8" MDL	0.34	0.21	0.36	58	2
	1-1/2" MDL	0.36	0.19	0.32	58	8
High-Performance™ Low-E4™ High Altitude 3.1mm / 13mm / 3.1mm	No Between-glass Grilles or MDL	0.36	0.24	0.41	55	8
	7/8" CDL	0.36	0.22	0.36	55	8
	1-1/8" & 1-1/2" CDL	0.36	0.19	0.32	55	8
	5/8" Between-glass Grilles	0.37	0.22	0.36	55	8
	1" Between-glass Grilles	0.37	0.22	0.36	55	8
	5/8" MDL	0.37	0.22	0.36	55	8
	7/8" MDL	0.37	0.22	0.36	55	8
	1-1/2" MDL	0.38	0.19	0.32	55	8
High-Performance™ Low-E4™ Gray Tint 3.1mm / 13mm / 3.1mm	No Between-glass Grilles or MDL	0.33	0.22	0.28	58	2
	7/8" CDL	0.33	0.20	0.25	58	2
	1-1/8" & 1-1/2" CDL	0.33	0.18	0.22	58	2
	5/8" Between-glass Grilles	0.34	0.20	0.25	58	2
	1" Between-glass Grilles	0.34	0.20	0.25	58	2
	5/8" MDL	0.34	0.20	0.25	58	2
	7/8" MDL	0.34	0.20	0.25	58	2
	1-1/2" MDL	0.36	0.18	0.22	58	8
High-Performance™ Low-E4™ Gray Tint High Altitude 3.1mm / 13mm / 3.1mm	No Between-glass Grilles or MDL	0.36	0.22	0.28	55	8
	7/8" CDL	0.36	0.20	0.25	55	8
	1-1/8" & 1-1/2" CDL	0.36	0.18	0.22	55	8
	5/8" Between-glass Grilles	0.37	0.20	0.25	55	8
	1" Between-glass Grilles	0.37	0.20	0.25	55	8
	5/8" MDL	0.37	0.20	0.25	55	8
	7/8" MDL	0.37	0.20	0.25	55	8
	1-1/2" MDL	0.38	0.18	0.22	55	8
High-Performance™ Low-E4™ Bronze Tint 3.1mm / 13mm / 3.1mm	No Between-glass Grilles or MDL	0.33	0.23	0.30	58	2
	7/8" CDL	0.33	0.20	0.27	58	2
	1-1/8" & 1-1/2" CDL	0.33	0.18	0.24	58	2
	5/8" Between-glass Grilles	0.34	0.20	0.27	58	2
	1" Between-glass Grilles	0.34	0.20	0.27	58	2
	5/8" MDL	0.34	0.20	0.27	58	2
	7/8" MDL	0.34	0.20	0.27	58	2
	1-1/2" MDL	0.36	0.18	0.24	58	8
	1-1/8" MDL	0.35	0.18	0.24	58	2

# Eagle Window & Door

## Ascent® Inswing French Door Sidelite with Handicap Sill (SL1)

2068 Tested Size at DP 40

Series 05 Ascent Clad Inswing French Door SL1 Sidelite H/C Sill

Glass Type	Divided Light Options	U-VAL	SHGC	VLT	CR	Energy Star Zone
High-Performance™ Low-E4™ Bronze Tint High Altitude 3.1mm / 13mm / 3.1mm	No Between-glass Grilles or MDL	0.36	0.23	0.30	55	8
	7/8" CDL	0.36	0.20	0.27	55	8
	1-1/8" & 1-1/2" CDL	0.36	0.18	0.24	55	8
	5/8" Between-glass Grilles	0.37	0.20	0.27	55	8
	1" Between-glass Grilles	0.37	0.20	0.27	55	8
	5/8" MDL	0.37	0.20	0.27	55	8
	7/8" MDL	0.37	0.20	0.27	55	8
	1-1/2" MDL	0.38	0.18	0.24	55	8
Low-E 240 3.1mm / 13mm / 3.1mm	No Between-glass Grilles or MDL	0.34	0.15	0.23	58	2
	7/8" CDL	0.34	0.13	0.20	58	2
	1-1/8" & 1-1/2" CDL	0.34	0.12	0.18	58	2
	5/8" Between-glass Grilles	0.35	0.13	0.20	58	2
	1" Between-glass Grilles	0.35	0.13	0.20	58	2
	5/8" MDL	0.35	0.13	0.20	58	2
	7/8" MDL	0.35	0.13	0.20	58	2
	1-1/2" MDL	0.36	0.12	0.18	58	8
Low-E 240 High Altitude 3.1mm / 13mm / 3.1mm	No Between-glass Grilles or MDL	0.36	0.15	0.23	55	8
	7/8" CDL	0.36	0.14	0.20	55	8
	1-1/8" & 1-1/2" CDL	0.36	0.12	0.18	55	8
	5/8" Between-glass Grilles	0.37	0.14	0.20	55	8
	1" Between-glass Grilles	0.37	0.14	0.20	55	8
	5/8" MDL	0.37	0.14	0.20	55	8
	7/8" MDL	0.37	0.14	0.20	55	8
	1-1/2" MDL	0.38	0.12	0.18	55	8
Low-E 366 3.1mm / 13mm / 3.1mm	No Between-glass Grilles or MDL	0.33	0.16	0.36	58	2
	7/8" CDL	0.33	0.14	0.32	58	2
	1-1/8" & 1-1/2" CDL	0.33	0.13	0.28	58	2
	5/8" Between-glass Grilles	0.34	0.14	0.32	58	2
	1" Between-glass Grilles	0.34	0.14	0.32	58	2
	5/8" MDL	0.34	0.14	0.32	58	2
	7/8" MDL	0.34	0.14	0.32	58	2
	1-1/2" MDL	0.35	0.13	0.28	58	2
Low-E 366 High Altitude 3.1mm / 13mm / 3.1mm	No Between-glass Grilles or MDL	0.36	0.16	0.36	56	8
	7/8" CDL	0.36	0.15	0.32	56	8
	1-1/8" & 1-1/2" CDL	0.36	0.13	0.28	56	8
	5/8" Between-glass Grilles	0.37	0.15	0.32	56	8
	1" Between-glass Grilles	0.37	0.15	0.32	56	8
	5/8" MDL	0.37	0.15	0.32	56	8
	7/8" MDL	0.37	0.15	0.32	56	8
	1-1/2" MDL	0.38	0.13	0.28	56	8
1-1/8" MDL	0.37	0.13	0.28	56	8	

U-Factor - Rate of Heat Loss = 1/R  
 SHGC - Solar Heat Gain Coefficient  
 VLT- Visible Light Transmittance  
 CR - Condensation Resistance