

Call Size	Width (Inches)	Height (Inches)	Vent Opening (Inches)			Sq. Ft. Daylight Opening	Glass Size (Inches)		Floor to Sill Height (Inches)
			Width	Projection	Sq. Ft. Vent		Width	Height	
2018	24	20	20 1/8	9 1/4	1.29	1.72	19	15	64 13/16
2020	24	24	20 1/8	9 1/4	1.29	2.22	19	19	60 13/16
2026	24	30	20 1/8	9 1/4	1.29	2.96	19	25	54 13/16
2030	24	36	20 1/8	9 1/4	1.29	3.71	19	31	48 13/16
2034	24	40	20 1/8	9 1/4	1.29	4.20	19	35	44 13/16
2040	24	48	20 1/8	9 1/4	1.29	5.20	19	43	36 13/16
2418	28	20	24 1/8	9 1/4	1.55	2.11	23	15	64 13/16
2420	28	24	24 1/8	9 1/4	1.55	2.72	23	19	60 13/16
2426	28	30	24 1/8	9 1/4	1.55	3.63	23	25	54 13/16
2430	28	36	24 1/8	9 1/4	1.55	4.54	23	31	48 13/16
2434	28	40	24 1/8	9 1/4	1.55	5.15	23	35	44 13/16
2440	28	48	24 1/8	9 1/4	1.55	6.36	23	43	36 13/16
2618	30	20	26 1/8	9 1/4	1.68	2.30	25	15	64 13/16
2620	30	24	26 1/8	9 1/4	1.68	2.96	25	19	60 13/16
2626	30	30	26 1/8	9 1/4	1.68	3.96	25	25	54 13/16
2630	30	36	26 1/8	9 1/4	1.68	4.95	25	31	48 13/16
2634	30	40	26 1/8	9 1/4	1.68	5.62	25	35	44 13/16
2640	30	48	26 1/8	9 1/4	1.68	6.94	25	43	36 13/16
2818	32	20	28 1/8	14 1/2	2.83	2.49	27	15	64 13/16
2820	32	24	28 1/8	14 1/2	2.83	3.21	27	19	60 13/16
2826	32	30	28 1/8	14 1/2	2.83	4.29	27	25	54 13/16
2830	32	36	28 1/8	14 1/2	2.83	5.37	27	31	48 13/16
2834	32	40	28 1/8	14 1/2	2.83	6.09	27	35	44 13/16
2840	32	48	28 1/8	14 1/2	2.83	7.52	27	43	36 13/16
3018	36	20	32 1/8	14 1/2	3.23	2.88	31	15	64 13/16
3020	36	24	32 1/8	14 1/2	3.23	3.71	31	19	60 13/16
3026	36	30	32 1/8	14 1/2	3.23	4.95	31	25	54 13/16
3030	36	36	32 1/8	14 1/2	3.23	6.20	31	31	48 13/16
3034	36	40	32 1/8	14 1/2	3.23	7.03	31	35	44 13/16
3040	36	48	32 1/8	14 1/2	3.23	8.69	31	43	36 13/16
3418	40	20	36 1/8	14 1/2	3.64	3.26	35	15	64 13/16
3420	40	24	36 1/8	14 1/2	3.64	4.20	35	19	60 13/16
3426	40	30	36 1/8	14 1/2	3.64	5.62	35	25	54 13/16
3430	40	36	36 1/8	14 1/2	3.64	7.03	35	31	48 13/16
3434	40	40	36 1/8	14 1/2	3.64	7.97	35	35	44 13/16
3440	40	48	36 1/8	14 1/2	3.64	9.85	35	43	36 13/16
4018	48	20	44 1/8	14 1/2	4.44	4.03	43	15	64 13/16
4020	48	24	44 1/8	14 1/2	4.44	5.20	43	19	60 13/16
4026	48	30	44 1/8	14 1/2	4.44	6.94	43	25	54 13/16
4030	48	36	44 1/8	14 1/2	4.44	8.69	43	31	48 13/16
4034	48	40	44 1/8	14 1/2	4.44	9.85	43	35	44 13/16
4040	48	48	44 1/8	14 1/2	4.44	12.18	43	43	36 13/16

Notes:

Approximate sash openings:

AFW<24" = 5-1/8"

AFW>24" and <32" = 9-1/4"

AFW>32" = 14-1/2"

Floor to sill height is based on structural header heights of 6' 10-1/2" and is calculated from the top of the subfloor to the top of the inside sill stop.

Code restrictions may vary depending on your local building codes.

If glass is positioned within 18" of the floor, safety/tempered glass may be required by code.

Eagle Window & Door reserves the right to change specifications without notice.